

10K VERSYMMETRIC® CL10V3

Equipped with 3-Stage directSPOT™ arms, an industry-first, the CL10V3 will reduce spotting time and boost productivity.

SERVICE BAY SPECIFICATIONS

- HEIGHT:** 12' minimum
- WIDTH:** 14' recommended
- DEPTH:** 24' recommended
- POWER:** 208-230v, 1pH, 30a

CONCRETE
4" thick, reinforced, free from cracks/seams, 3500+ psi & cured 28+ days



PRODUCT SPECIFICATIONS

MODEL NUMBER	CL10V3	CL10V3-QC
Description	Versymmetric®	Versymmetric® w/ QuickCycle™
Lifting Capacity	10,000 lbs.	
Lift Configuration	Versymmetric®, 3-Stage Front & Rear	
Rise Height	74⅞"	
Height of Columns	Standard 11' 8" or 11' 2" with 2' or 3' extensions	
Max. Extended Cylinder Height	11' 11"	
Adjustable Width Overall (A)	11' 6½" - 11' 11"	
Drive Thru Clearance	8' 4" / 8' 8½"	
Floor to Overhead Switch	Standard 11' 2½" or 10' 8½" with 2' or 3' extensions	
Front Arm Reach	Min. 20" Max. 42"	
Rear Arm Reach	Min. 37⅝" Max. 60"	
Screw Pad Height	Min. 3⅞" Max. 6⅞"	
Inside Columns (B)	Min. 9' 2" Max. 9' 6½"	
Low Lock Height	12" Net Rise	
Platform Length	NA	
Rise Time	38s	24s
Max. Load per Arm	2,500 lb.	
ALI® Certified	<input checked="" type="checkbox"/>	

SERVICE BAY LAYOUT

